




The SL-C510 is a high intensity, completely self-contained 5–9NM solar LED marine lantern. The range is available in three chassis sizes with satellite connectivity offered as an option.

Key Features:

- Intensity Range of 5-9NM+
- Enhanced Optics
- High performance, premium-grade solar modules with active MPPT
- Satellite Communications Enabling Two-Way Monitoring
- Bluetooth® Connectivity
- Integrated, Internal AIS Type 1



Intensity Range

The SL-C510 lantern range utilise leading technology LEDs for a visible range of 5-9NM.

Enhanced Optics

The optics and lens design ensures that vessel operators can clearly see the light from above when passing the AtoN.

Solar Efficiency

Designed with next generation solar technology including individual active MPPT (maximum power point tracking), maximising the power extracted from the solar panels for improved performance and efficiency.

OLED Screen with Touchpad


The conveniently located OLED (Organic Light-Emitting Diode) screen with touchpad allows maintenance personnel to check the diagnostics of the lantern with the touch of a button.

SL-C510_DATA_EN_V2.3

Accessible Via Star2M

The SL-C510 range is available with an optional integrated Iridium® Satellite module enabling two-way monitoring and control using the Iridium® Low Earth Orbit satellite network.

Available in three chassis sizes (compact, extended or AIS) to accommodate larger battery capacity and additional solar charging capability.



SL-C510

Compact

Extended

AIS Chassis

Light Characteristics

Light Source	LED		
Available Colours	Red, Green, White, Yellow, Blue		
SL-C510-5D Typical Maximum Intensity (cd) [†]	Red - 620, Green - 690, White - 1150, Yellow - 570, Blue - 310		
SL-C510-10D Typical Maximum Intensity (cd) [†]	Red - 460, Green - 440, White - 650, Yellow - 320, Blue - 200		
Visible Range (NM)	AT @ 0.74: 5-9NM		
Horizontal Output (degrees)	360		
Vertical Divergence (degrees)	5 or >10		
Available Flash Characteristics	Up to 310 IALA recommended (user adjustable)		
Intensity Adjustments	Multiple intensity settings		
LED Life Expectancy (hours)	>100,000		

Electrical Characteristics

Current Draw (mA)	Refer to Sealite Solar Calculator		
Circuit Protection	Integrated		
Nominal Voltage (V)	12		
Autonomy (nights)	>110 (14 hour darkness, 12.5% duty cycle)		

Solar Characteristics

Solar Module Type	Monocrystalline		
Output (watts)	20.0 (4 x 5 watt)	33.6 (4 x 8.4 watt)	33.6 (4 x 8.4 watt)
Charging Regulation	MPPT		

Power Supply

Battery Type	Gel SLA		
Battery Capacity (Ah)	12	24	24

Physical Characteristics

Body Material	Aluminium chassis with UV-stabilised rubber corners & gaskets. Polymer composite-moulded top and base		
Lens Material	LEXAN® Polycarbonate – UV-stabilised		
Lens Diameter (mm/inches)	98 / 3 7/8		
Lens Design	LED Optic		
Mounting	3 & 4 hole 200mm bolt pattern		
Height (mm/inches)	492 / 19.37	648 / 25.50	660 / 25.98
Width (mm/inches)	234 / 9.05	234 / 9.05	234 / 9.05
Mass (kg/lbs)	9.2 / 20.3	15.2 / 33.5	16.0 / 35.3
Service Life	15 years ^		

Environmental Standards

Shock	MIL-STD-202G Test Condition H, Method 213B 30G vertical and 35G horizontal shock		
Vibration	MIL-STD-202G, Test Condition B, Method 204D 5G in all axes		
Ice Loading	Rated to withstand 22kg/m ²		
Salt Fog	MIL-STD-810F Method 509.4		
Rain Test	MIL-STD-810F Method 506.4 procedure 1		
Wind Exposure	Rated to withstand 140 knots		
Humidity	MIL-STD-810F method 507.4 (0 – 100%, condensing)		
Temperature Range	-30 to 50°C		

Compliance

CE	EN61000-6-2:2005, IEC61000-4-2:2008, IEC61000-4-3:2010, IEC61000-6-1:2016		
IALA	Signal colours compliant to IALA E-200-1		
Ingress Protection	IP68		

Intellectual Property

Trademarks	SEALITE® is a registered trademark of Sealite Pty Ltd		
Warranty *	3 years		
Options Available	<ul style="list-style-type: none"> • IR Programmer • External ON/OFF Switch 	<ul style="list-style-type: none"> • External Battery Charging Port • Satellite Communications 	<ul style="list-style-type: none"> • 5°, 10° Lens • AIS Type 1




• Specifications subject to change or variation without notice
[†] Intensity setting subject to solar availability

* Subject to standard terms and conditions

^ Refer to the Sealite website under the warranty section

SL-C510_DATA_EN_V2.3

Technical Illustrations



Ordering This Product

SL-C510-[XXD]-[XXXX]-[X]-[XX]



1 Product Number

2 Lens Type

- 05 (5 Degree)
- 10 (10 Degree)

3 Chassis Configuration

- S2C0 (Compact)
- S2C2 (Extended)
- S2A2 (AIS)

4 LED Option:

- W White
- Y Yellow
- G Green
- R Red
- B Blue
- BY Blue-Yellow

5 Option Configuration

- 00 No Options
- 01 Charge Port
- 02 Switch
- 03 Charge Port and Switch
- 04 SAT Only
- 05 SAT with Switch
- 06 SAT with Charge Port
- 07 SAT with Charge Port and Switch
- 08 GSM Only
- 09 GSM with Switch
- 10 GSM with Charge Port
- 11 GSM with Charge Port and Switch
- 14 AIS Type 1 with Charge Port




Want to monitor, maintain, manage and control your assets? [Click here](#)



· Specifications subject to change or variation without notice
 * Subject to standard terms and conditions
 † Intensity setting subject to solar availability
 ^ Refer to the Sealite website under the warranty section

SL-C510_DATA_EN_V2.3



SL_C510_DATA_EN_V2.3



[sealite.com](https://www.sealite.com)

Head Office
+61 (0)3 5977 6128

Americas
+1 (603) 737 1311

UK
+44 (0)1502 588026

Asia
+65 6908 2917