



MARINE-MOLY™ AEROSOL

MOLYBDENUM DISULFIDE LUBRICANT

DESCRIPTION

MARINE-MOLY™ is a specially formulated Molybdenum Disulfide (MoS₂) and graphite marine lubricating paste that provides a low-friction shield by “plating” to metal surfaces to reduce bearing temperature, protect working parts, prevent galling and heat freeze.

MARINE-MOLY is water resistant to withstand extreme weather elements and helps prevent corrosion on metal exposed to water, steam, salt spray, etc. **MOLY DISULFIDE** has a 300,000-psi film strength.

- Lead Free
- Service rating: -300°F (-185°C) to 750°F (400°C)
- Water Resistant
- Non-melting
- Contains Moly
- Color - Black
- Convenient aerosol package

APPLICATIONS

- Highly Opened Gears
- Loading Racks & Arms
- Marine Transmission Gears
- Open Spur Gears
- Sliding Bases

PRODUCT CHARACTERISTICS

VOC Content (Includes Propellant)	402 g/Liter
Propellant	Hydrocarbon
Spray Pattern	2” - 4” Cone
NFPA 30B Storage Class	Level III
Color	Black
Thickener Type	Lithium
Base Oil Type	Petroleum
Penetration (ASTMD-217)	275 – 305
Density (lb./gal)	8.76
Specific Gravity	1.05
Flash Point (ASTM D-92)	> 550°F (288°C)
Shell 4-Ball (ASTMD-2596)	
Weld Point, kg	315
Load Wear Index	66.21
Wear Scar (ASTMD-2266)	0.617
Copper Strip Corrosion (ASTMD-4048)	1B
Water Spray Off Resistance (ASTMD-4049)	<40%

For package types and part numbers contact sales@jetlube.com.

LIMITED WARRANTY

For warranty information please visit

http://www.jetlube.com/pdf/Jet-Lube_Warranty.pdf

You can also email us at sales@jetlube.com or write to the Sales Department at the address below.