

DESCRIPTION

Wire ropes contain numerous moving parts that require lubrication. Each time the rope bends or flexes, the internal strands rub together. **WRL**[™] coats these strands with a nearly VOC-free lubricant to prevent friction and wear. This results in longer life, less downtime for rope changes and more production.

JET-LUBE'S WIRE ROPE and CHAIN LUBRICANT quickly penetrates to the cores. This ensures that the rope is lubricated throughout while providing a nondrying, non-tacky film on the outside of the rope that protects outer strands from corrosion, as well as lubricating the wire rope drums and sheaves.

WRL is pumpable at temperatures down to -25°F (-32°C) Its nondrying film remains flexible in most extreme weather conditions, which eliminates flaking and peeling.

- Lead Free
- Prolongs wire rope life
- Non-tacky
- Pumpable
- Displaces water
- Protects against rust and corrosion
- Flexible finish
- Convenient Aerosol package

APPLICATIONS

WRL can be used to lubricate all sizes of wire rope, as well as chains, leaf springs and other applications where a penetrating oil is needed.

SERVICE RATING -25°F (-32°C) to 350°F (175°C)

WRL Wire Rope Lubricant

Contains no 1.1.1 Trichloroethane, Freon TF or other ozone harming ingredients.

PRODUCT CHARACTERISTICS

Spray Pattern Propellant Solvent Type Fluid Type Specific Gravity Density (lbs/gal) Viscosity, (ASTM D-445) cSt @ 40°C Pour Point, (ASTM D-97) Rust Test, (ASTM D-665) Flash Point (ASTM D-92) Color/Appearance Spray Pattern Propellant Solvent Type Dielectric Strength (ASTM D-877) VOC Content NFPA 30 B Storage Class Tight Stream Carbon Dioxide LVP Petroleum Distillate Petroleum Oil 0.83 6.9

4.5 – 6.0 <40°F(-40°C) A. Pass >176°F(79°C) Amber Tight Stream Carbon Dioxide Petroleum Distillate 35 kv

Nil (LVP solvent) Level II

For package types and part numbers contact <u>sales@jetlube.com</u>

LIMITED WARRANTY

For warranty information please visit http://www.jetlube.com/pdf/Jet-Lube Warranty.pdf

You can also email us at <u>sales@jetlube.com</u> or write to the Sales Department at the address below.