

911

High Temperature Thermosetting Compound

Description: Black color, extremely dense, fibrous putty, impregnated with metal and ceramic fibers.

Temperature Range: 200°F (93°C) to 1600°F (871°C)

Applications: Clamps, Enclosures, Perimeter Seals, Wire Wraps, Flanges. Designed bad blows. Can be used for killing or plugging valves or lines no longer in use. (Not for use as a valve packing.)

Chemical Compatibility: Non-reactive to most volatile organic compounds, solvents, acids, alkalis, and corrosive gases.

Compatible For Use: Steam, Boiler Feed Water, Condensate, Gasoline, Alcohols, Benzene, Butane, Carbon Dioxide, Fuel Oils, Hydrocarbons, Hydrogen, Ketones, Synthetic Gases, Oils, Etc.

Characteristics: Fast and hard-setting injectable sealant. Outstanding plugging capabilities. Because of its accelerated curing time it will not wash out like conventional sealants.

Shelf Life: 6 months in closed packages. Recommend refrigerator or freezer storage.

Packaged: J-Sticks, 5/8" x 3" Plugs

Procedure Warning: (For industrial use by professionally trained personnel only) If being injected, steps should be taken to insure that the injection pressure in conjunction with pressure that may occur from gassing off of the compound does not exceed the pressure limitations of the piping system. If the compound is gassing off, gasses should be vented. Also, be aware it is quite common that the application temperature will exceed the compound flash point. Be aware of the possibility of a flash and take necessary precautions. See SDS for personal protective equipment. Refer to product SDS and technical data for reactivity and compatibility information.

FOR INDUSTRIAL USE BY PROFESSIONALLY TRAINED PERSONNEL ONLY.

CONSULT MSDS & TECH SHEET FOR ALL SAFETY, TECHNICAL, & WARRANTY INFORMATION BEFORE USE.

NOT RECOMMENDED FOR USE ON NUCLEAR APPLICATIONS

Disclaimer: The information & recommendations of Jet-Lube LLC / Deacon concerning these products is based upon laboratory tests, customer feedback, and experience and to the best of our knowledge and belief are true and accurate. As the conditions of use are beyond the control of Jet-Lube LLC / Deacon, the company assumes no liability for damage caused by this product other than the replacement of the product or refund of the purchase price. The responsibility for determining whether or not the product is suitable for use rest solely with the purchaser. Jet-Lube LLC / Deacon recommends that the product be tested prior to use. This product is intended for a temporary repair and no agent, representative or employee of the company is authorized to alter this provision which relates to goods delivered, whether sold, delivered as samples or otherwise.

sales@deaconindustries.com (800) 552-2896 or (724) 225-8008