



Max Single-Use Earplug

Highest attenuation in single-use earplugs

[Learn more about our products at howardleight.com >](http://howardleight.com)
[Learn more about hearing conservation at hearforever.org >](http://hearforever.org)



Overview

Key Features

- The world's most-used polyurethane foam earplug
- Bell shape delivers maximum in-ear comfort
- Contoured design easier to insert, resists tendency to back-out of ear canal
- Polyurethane foam enhances comfort, especially for long-term wear
- Smooth, soil-resistant closed cell-foam skin prevents dirt build-up
- Bulk refills for Leight Source 400 and Leight Source 500 Earplug Dispensers save time, waste and space

Recommended Industries/Use

- Agriculture
- Chemical
- Construction
- Fire Protection
- Forestry
- Government
- Law Enforcement
- Manufacturing
- Medical
- Military
- Mining
- Municipal Services
- Oil and Gas

Max Single-Use Earplug

- Pharmaceutical
- Steel and Metals
- Transportation
- Utilities
- Welding

Hazards

- Noise

Regulations

- 29 CFR 1910.95 - OSHA Occupational Noise Exposure (US)
- ANSI S3.19-1974 - Attenuation Test Protocol (US)
- Part II, (R.S.C. 1985, c. L-2) - Canada Labour Code
- Z94.2-1994 - Attenuation Test Protocol (CAN)
- 2003/10/EC - EU Hearing Directive
- 89/686/EEC - EC Directive/PPE
- Category II - EC Category/PPE
- EN 352-2:2002 - EU Standards
- NOHSC: 1007 (2000) - National Standard for Occupational Noise (AUS/NZ)
- NR 15 - Security and Health of Work, Annexes 1 and 2, n°3.214/1978 - Occupational Noise Regulations (BR)
- ANSI S12.6/1997 - Method B - Attenuation Test Protocol (BR)

Historical Brand

Howard Leight

Specifications

Color	Coral
Shape	Bell
Material	Polyurethane Foam
Packaging Options	• Polybag • Paper Bag • Bulk Refill for Leight Source 400 or Leight Source 500 Dispenser
Cord Options	• Uncorded • Polycord
NRR	33
Canada Class	A(L)
SNR	37
SLC80	26 dB / Class 5

EU Certifications

- European Directives – 89/686/EEC
- EC Category PPE – Category II
- Standards – EN 352-2:2002
- EC Certification Number – 1219
- EC Attestation Number – 040366
- Laboratory – INSPEC
-

AUS Certifications

- Standardsmark License #1579

SKUs & Ordering Information

SKUs	Details
MAX-30	Max - corded NRR 33 Canada Class A(L)
MAX-30-PB	Max - corded / paper bag NRR 33 Canada Class A(L)
MAX-1	Max - uncorded NRR 33 Canada Class A(L)
MAX-5	Max - uncorded / 5 pair pack NRR 33 Canada Class A(L)
MAX-1-PB	Max - uncorded / paper bag NRR 33 Canada Class A(L)
MAX-LS4	Max - uncorded bulk refill for Leight Source 400 NRR 33 Canada Class A(L)
MAX-1-D	Max - uncorded bulk refill for Leight Source 500 NRR 33 Canada Class A(L)

Training & Proper Use

1. With clean hands, roll the entire earplug into narrowest possible crease-free cylinder.
2. Reach over your head with a free hand, pull your ear up and back, and insert the earplug well inside your ear canal.
3. Hold for 30 – 40 seconds, until the earplug fully expands in your ear canal. If properly fitted, the end of the earplugs should not be visible to someone looking at you from the front.
4. Proper Fit – If either or both earplugs do not seem to be fitted properly, remove the earplug and reinsert.
5. Removal – Gently twist earplug while slowly pulling in an outward motion for removal.
6. Acoustical Check – In a noisy environment, with earplugs inserted, cup your hands over your ears and release. Earplugs should block enough noise so that covering your ears with your hands should not result in a significant noise difference.

Additional Information

CARE + MAINTENANCE

- INSPECT – Inspect prior to fitting, examine your earplugs for dirt, damage or extreme hardness—discard immediately if compromised.
- DISCARD – For proper hygiene, discard Single-Use earplugs after use.
- HYGIENE – To maintain hygiene standards, Single-Use earplugs should be discarded at the end of every shift.

RELATED PRODUCTS



For general inquiries
800.343.3411

View other Sperian Sites
© 2010 Sperian Protection