

SAE 15W-40**Gasoline and Diesel engine oil****TYPE OF USE**

Designed for the old generation of Gasoline and Diesel engines.
Suitable for all types of fuel (i.e. standard, unleaded, Diesel fuel, LPG) and with the use of catalytic converter.
All driving conditions: City, Road, Highway.

PERFORMANCES**STANDARDS** API SF / CD

Detergent and dispersing agents to keep the engine clean.
Efficient anti-wear additivation to increase engine's longevity.
Anti-oxidation properties.
Anticorrosion, Anti-foam properties.

RECOMMENDATIONS

Drain interval : according to manufacturers' requirements and adjust according to your own use.
MOTUL SAE 15W-40 can be mixed with synthetic or mineral oils.

PROPERTIES

Viscosity grade	SAE J 300	15W-40
Density at 20°C (68°F)	ASTM D1298	0.875
Viscosity at 40°C (104°F)	ASTM D445	110.0 mm ² /s
Viscosity at 100°C (212°F)	ASTM D445	14.5 mm ² /s
Viscosity Index	ASTM D2270	135.0
Pour point	ASTM D97	-27.0 °C / -17.0 °F
Flash point	ASTM D92	224.0 °C / 435.0 °F

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty. Made in FRANCE

MOTUL - 119 Bd Félix Faure - 93303 - AUBERVILLIERS CEDEX - BP 94 - Tel: 33 1 48 11 70 00 - Fax: 33 1 48 33 28 79 - www.motul.com



SAE 15W-40

Gasoline and Diesel engine oil

TBN

ASTM D2896

10.2 mg KOH/g

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty. Made in FRANCE

MOTUL - 119 Bd Félix Faure - 93303 - AUBERVILLIERS CEDEX - BP 94 - Tel: 33 1 48 11 70 00 - Fax: 33 1 48 33 28 79 - www.motul.com